



Item # _____

Job _____



Laboratory Solutions — Just Add Casters

Metro® LAB SOLUTIONS

Metro's new line of laboratory solutions address a wide range of laboratory requirements while providing a superior level of corrosion resistance. Built from advanced polymers that include *Microban® antimicrobial product protection, Metro's innovative MetroMax and Deep Ledge designs provide the ideal product platform. Available product solutions are modular by design and offer the customer ultimate flexibility by permitting the end user to select the most appropriate caster based on their budget and/or application requirements. Metro's Polymer Laboratory Solutions include:

- Lab Worktables and Accessories
- Antimicrobial Casters
- Glassware Handling Solutions
- High Performance Liquid Chromatography Solutions
- General Lab Cart
- Chemical Transport Cart
- Mobile Desk
- Deep Ledge Lab Carts
- Deep Ledge Lab Dolly

Both MetroMax and Deep Ledge shelves have built-in Microban® antimicrobial product protection. Microban protects the shelf mats from bacteria, mold, mildew and fungi that cause odors, stains and product degradation.

- **Corrosion Resistant:** MetroMax shelves and posts are designed to withstand rust and corrosion over the life of the product, so they are perfectly suited for damp and humid conditions. MetroMax shelves and posts come with a lifetime warranty against rust and corrosion.
- **Cleans Easily:** Solid MetroMax and Deep Ledge shelves contain spills and wipe down easily. Shelf frame and posts are smooth and rounded with no sharp edges so they wipe down easily.
- **Strong and Durable:** Reinforced polymers give MetroMax incredible strength — up to 800 lbs. (364kg) per shelf. Deep Ledge shelf load rating depends on application.



MetroMax Lab Worktable (Shown with accessories, casters and Starsys Cart)



MetroMax 4 Basket Glassware Cart (Shown with casters and accessories)



Deep Ledge Lab Dolly (Shown with stainless casters)

*MICROBAN is a registered trademark of Microban Products Company.



InterMetro Industries Corporation
North Washington Street
Wilkes-Barre, PA 18705
www.metro.com



52.01



LABORATORY SOLUTIONS — JUST ADD CASTERS

Specifications

MetroMax®:

Longitudinal Beams and Posts: Pultrusions — continuous glass fibers and thermoset resin composite.
Mats, Open and Solid: Mineral reinforced polypropylene. Mats contain Microban® antimicrobial product protection.

Ledges, Dividers, and Wedge: Glass reinforced polypropylene.
Post Cap and Center Beam Cap: High-density polyethylene. MetroMax is applicable in cooler conditions down to -20°F (-29°C).

Countertop (Lab Worktables):

Stainless Steel Top: 16 gauge (.060) thk, Type 304 Stainless Steel, #3 Polish with vinyl protection. Bull nose front edge and 4" (102mm) high brake-formed backsplash.

Phenolic Top: TRESPA Top Lab Plus (black or gray) phenolic resin.
Phenolic Backsplash: TRESPA Athlon (black or gray) phenolic resin.

MetroMax Lab Worktables

- Advanced polymer construction provides excellent corrosion-resistance performance for the most corrosive lab environments.
- Table features smooth surfaces that are easy-to-clean. Mobile units can be easily moved to clean behind table area.
- Available top materials include Type 304 stainless and TRESPA phenolic resin (black or gray). Refer to chart below for more information.
- Choose from a wide range of available accessories and caster options (page 3) to customize table for a specific application.

Countertop Application Matrix

Use Area	Epoxy Resin	Phenolic Resin	Stainless Steel	Characteristics	Epoxy Resin	Phenolic Resin	Stainless Steel
				Heat Resistance	Excellent	Fair*	Excellent
				Abrasion Resistance	Good	Excellent	Good
Low chemical use				Impact Resistance	Good	Excellent	Good
Moderate chemical use	X	X		Strength	Good	Excellent	Good
High chemical use		X	X	Stain Resistance	Good	Good	Good

*Discolors with high heat

Note: Phenolic resin and stainless are offered as top options for this table system. **Epoxy resin information is shown for comparison only.**

Definitions:

Phenolic resin: Compression molded of organic fiber-reinforced phenolic core with an integrally cured thermoset resin surface. Stronger than Epoxy resin over a span, and not as brittle.

Stainless Steel: Worksurfaces are fabricated from Type 304 stainless steel which provides excellent protection in corrosive environments.

Epoxy resin: Epoxy resins, silica, organic fillers, and inert hardeners are cast in forms and cured to a uniform mixture throughout.

Select Table Style from Chart Below and Following Page:

Worktables with Stainless Top and Solid MetroMax Shelf

Cat. No. Stationary	Cat. No. Mobile*	Width		Length		Work Surface Height		Overall Height		Approx. Pkd. Wt.	
		(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	(lbs.)	(kg)
LT30XS	LTM30XS	30	762	29 ³ / ₄	749	35 ¹ / ₂	902	39 ¹ / ₂	1003	65	29
LT36XS	LTM36XS	30	762	35 ³ / ₄	908	35 ¹ / ₂	902	39 ¹ / ₂	1003	70	32
LT48XS	LTM48XS	30	762	47 ³ / ₄	1213	35 ¹ / ₂	902	39 ¹ / ₂	1003	90	41
LT60XS	LTM60XS	30	762	59 ³ / ₄	1517	35 ¹ / ₂	902	39 ¹ / ₂	1003	100	45

*Casters ordered separately. Refer to Caster Selection Guide (page 3) for caster options.

Note: Lab Worktables are load rated at 50 lbs. (23kg) per square foot up to a maximum of 600 lbs. (273kg), assuming load evenly distributed.

Worktables with Stainless Top and 3-Sided Frame

Cat. No. Stationary	Cat. No. Mobile*	Width		Length		Work Surface Height		Overall Height		Approx. Pkd. Wt.	
		(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	(lbs.)	(kg)
LT30XUS	LTM30XUS	30	762	29 ³ / ₄	749	35 ¹ / ₂	902	39 ¹ / ₂	1003	70	32
LT36XUS	LTM36XUS	30	762	35 ³ / ₄	908	35 ¹ / ₂	902	39 ¹ / ₂	1003	75	34
LT48XUS	LTM48XUS	30	762	47 ³ / ₄	1213	35 ¹ / ₂	902	39 ¹ / ₂	1003	95	43
LT60XUS	LTM60XUS	30	762	59 ³ / ₄	1517	35 ¹ / ₂	902	39 ¹ / ₂	1003	110	50

*Casters ordered separately. Refer to Caster Selection Guide (page 3) for caster options.

Note: Lab Worktables are load rated at 50 lbs. (23kg) per square foot up to a maximum of 600 lbs. (273kg), assuming load evenly distributed.



LTM48XUPG
(Shown with accessories, casters and Starsys Cart)



LTM30XS
(Shown with casters)



LTM30XUS
(Shown with accessory wire shelf and casters)

LABORATORY SOLUTIONS — JUST ADD CASTERS



MetroMax Lab Worktables (cont'd)

Select Table Style from Chart Below:

Worktables with Black Phenolic Top and Solid MetroMax Shelf

Cat. No. Stationary	Cat. No. Mobile*	Width (in.) (mm)	Length (in.) (mm)	Work Surface Height (in.) (mm)	Overall Height (in.) (mm)	Approx. Pkd. Wt. (lbs.) (kg)
LT30XPB	LTM30XPB	30 762	29 ³ / ₄ 749	36 ¹ / ₂ 927	40 ¹ / ₂ 1016	85 38
LT36XPB	LTM36XPB	30 762	35 ³ / ₄ 908	36 ¹ / ₂ 927	40 ¹ / ₂ 1016	91 41
LT48XPB	LTM48XPB	30 762	47 ³ / ₄ 1213	36 ¹ / ₂ 927	40 ¹ / ₂ 1016	118 53
LT60XPB	LTM60XPB	30 762	59 ³ / ₄ 1517	36 ¹ / ₂ 927	40 ¹ / ₂ 1016	138 62

*Casters ordered separately. Refer to Caster Selection Guide (page 3) for caster options.

Note: Lab Worktables are load rated at 50 lbs. (23kg) per square foot up to a maximum of 600 lbs. (273kg), assuming load evenly distributed.



LTM48XPB
(Shown with back splash accessory and casters)

Worktables with Black Phenolic Top and 3-Sided Frame

Cat. No. Stationary	Cat. No. Mobile*	Width (in.) (mm)	Length (in.) (mm)	Work Surface Height (in.) (mm)	Overall Height (in.) (mm)	Approx. Pkd. Wt. (lbs.) (kg)
LT30XUPB	LTM30XUPB	30 762	29 ³ / ₄ 749	36 ¹ / ₂ 927	40 ¹ / ₂ 1016	90 41
LT36XUPB	LTM36XUPB	30 762	35 ³ / ₄ 908	36 ¹ / ₂ 927	40 ¹ / ₂ 1016	97 44
LT48XUPB	LTM48XUPB	30 762	47 ³ / ₄ 1213	36 ¹ / ₂ 927	40 ¹ / ₂ 1016	125 56
LT60XUPB	LTM60XUPB	30 762	59 ³ / ₄ 1517	36 ¹ / ₂ 927	40 ¹ / ₂ 1016	145 66

*Casters ordered separately. Refer to Caster Selection Guide (page 3) for caster options.

Note: Lab Worktables are load rated at 50 lbs. (23kg) per square foot up to a maximum of 600 lbs. (273kg), assuming load evenly distributed. Worktables with Black Phenolic Top and 3-Sided Frame



LTM48XUPB
(Shown with accessories and casters)

Worktables with Gray Phenolic Top and Solid MetroMax Shelf

Cat. No. Stationary	Cat. No. Mobile*	Width (in.) (mm)	Length (in.) (mm)	Work Surface Height (in.) (mm)	Overall Height (in.) (mm)	Approx. Pkd. Wt. (lbs.) (kg)
LT30XPG	LTM30XPG	30 762	29 ³ / ₄ 749	36 ¹ / ₂ 927	40 ¹ / ₂ 1016	85 38
LT36XPG	LTM36XPG	30 762	35 ³ / ₄ 908	36 ¹ / ₂ 927	40 ¹ / ₂ 1016	91 41
LT48XPG	LTM48XPG	30 762	47 ³ / ₄ 1213	36 ¹ / ₂ 927	40 ¹ / ₂ 1016	118 53
LT60XPG	LTM60XPG	30 762	59 ³ / ₄ 1517	36 ¹ / ₂ 927	40 ¹ / ₂ 1016	138 62

*Casters ordered separately. Refer to Caster Selection Guide (page 3) for caster options.

Note: Lab Worktables are load rated at 50 lbs. (23kg) per square foot up to a maximum of 600 lbs. (273kg), assuming load evenly distributed. Worktables with Black Phenolic Top and 3-Sided Frame



LTM48XPG
(Shown with back splash accessories and casters)

Worktables with Gray Phenolic Top and 3-Sided Frame

Cat. No. Stationary	Cat. No. Mobile*	Width (in.) (mm)	Length (in.) (mm)	Work Surface Height (in.) (mm)	Overall Height (in.) (mm)	Approx. Pkd. Wt. (lbs.) (kg)
LT30XUPG	LTM30XUPG	30 762	29 ³ / ₄ 749	36 ¹ / ₂ 927	40 ¹ / ₂ 1016	90 41
LT36XUPG	LTM36XUPG	30 762	35 ³ / ₄ 908	36 ¹ / ₂ 927	40 ¹ / ₂ 1016	97 44
LT48XUPG	LTM48XUPG	30 762	47 ³ / ₄ 1213	36 ¹ / ₂ 927	40 ¹ / ₂ 1016	125 56
LT60XUPG	LTM60XUPG	30 762	59 ³ / ₄ 1517	36 ¹ / ₂ 927	40 ¹ / ₂ 1016	145 66

*Casters ordered separately. Refer to Caster Selection Guide (page 3) for caster options.

Note: Lab Worktables are load rated at 50 lbs. (23kg) per square foot up to a maximum of 600 lbs. (273kg), assuming load evenly distributed. Worktables with Black Phenolic Top and 3-Sided Frame



LTM48XUPG
(Shown with accessories and casters)

For Mobile Lab Tables, Select Appropriate Casters from Chart Below. (Four brake casters are recommended for maximum table stability)

Caster Selection Guide						Load Rating (lbs.) (kg)	Corrosion Resistance	Cart Washable	Antimicrobial Additive in Wheel
*Caster Series	Wheel Material	Rollability	Floor Protection	Noise					
5MDXA/5MDBXA (brake)	High Modulus Rubber	Good	Good	Low	250 114	Low	No	No	
5MPX/5MPBX (brake)	Polyurethane	Good	Good	Moderate	300 137	Low	No	No	
5PCX/5PCBX (brake)	Polyurethane	Good	Good	Moderate	300 137	High	No	No	
5PCXM/5PCBXM (brake)	Polyurethane	Good	Good	Moderate	300 137	High	No	Yes	
5MPXGSA/5MPXGSA (brake)	Polyurethane	Good	Good	Moderate	300 137	High	Yes	No	

*Casters listed are for use with MetroMax product solutions. For Super Erecta post applications, including Deep Ledge Lab Cart and Lab Dolly applications, use part number listed above minus "X" designation.
NOTE: The total weight of the equipment and its load should not exceed three times the load rating per caster.
Additional stem casters, in various sizes and wheel materials, are available. Contact your Metro rep for more information.

See page 4 for caster photos.

See page 3 for Caster Selection Guide.




5MDXA 5PCBX 5MPX 5PCBXM

Additional MetroMax Accessory Options

Handle



Ledges



Dividers



Label Holders



Color Shelf Markers



For more information on those and other MetroMax accessories, contact your Metro representative.

Metro Totes



Choose from Available Accessories to Customize Table.

Backsplash

4" (102mm) high. Attaches to phenolic table top (page 3), using pre-drilled holes. Match length and color with selected countertop.



L30BSG

Cat. No. Black	Cat. No. Gray	Length (in.) (mm)		Approx. Pkd. Wt. (lbs.) (kg)	
LT30BSB	LT30BSG	27 ³ / ₄	705	5.5	2.5
LT36BSB	LT36BSG	33 ³ / ₄	875	6.5	2.9
LT48BSB	LT48BSG	45 ³ / ₄	1162	7.5	3.4
LT60BSB	LT60BSG	57 ³ / ₄	1466	9.5	4.3

Keyboard Tray

Cat. No. LTKB



Drawers

Cat. No. LTD3

3" (76mm)

Cat. No. LTD6

6" (152mm)

Cat. No. LTD3L


3" (76mm) locking

Cat. No. LTD6L — 6" (152mm) locking



Wire Shelf

Stainless or Epoxy-coated shelves available.



Cat. No. Stainless	Cat. No. Epoxy Coated	Length (in.) (mm)		Approx. Pkd. Wt. (lbs.) (kg)	
LT30WS	LT30WE	22 ³ / ₈	568	6	2.7
LT36WS	LT36WE	28 ³ / ₈	720	7.5	3.4
LT48WS	LT48WE	40 ³ / ₈	1025	10	4.5
LT60WS	LT60WE	52 ³ / ₈	1330	12	5.4

Note: Shelves are load rated for a maximum of 150 lbs. (68kg).

Surface Mount Swing Arm for Flat Monitor

Cat. No. LTFMA





MetroMax® Glassware Carts

- Two-basket and four-basket capacity glassware solutions are offered in a space-saving 18" x 36" (457 x 914mm) footprint.
- Solid MetroMax bottom shelf provides spill retention and can be removed from shelf frame for easy cleaning.
- Glassware carts are built, primarily, from MetroMax advanced polymers, providing lifetime corrosion protection.
- Choose from a wide range of accessories, including all-polymer casters, for maximum corrosion resistance and premium performance.

Refer to Caster Selection Guide (page 3) for choice of casters. Units listed below do not include casters. Metro's 5PC series (two brake, two swivel) casters are recommended for superior lifetime performance.

Cat. No.	Width		Length		Height		Description	Approx. Pkd. Wt.	
	(in.)	(mm)	(in.)	(mm)	(in.)	(mm)		(lbs.)	(kg)
GWB1	18	457	36	914	40	1016	2-Basket Unit	38	17
GWB2	18	457	36	914	60	1524	4-Basket Unit	83	37
GWT1	18	457	36	914	40	1016	2-Tote Kit Unit	36	16.3
GWT2	18	457	36	914	60	1524	4-Tote Kit Unit	101	46



Accessories

Cat. No.	Width		Length		Height		Description	Approx. Pkd. Wt.	
	(in.)	(mm)	(in.)	(mm)	(in.)	(mm)		(lbs.)	(kg)
GWVC41	18	457	36	914	32	889	Clear Cart Cover — Short Unit	2.5	1.1
GWVC62	18	457	36	914	52	1320	Clear Cart Cover — Tall Unit	3.5	1.6
GWSVC41	18	457	36	914	32	889	Blue Cart Cover — Short Unit	2.5	1.1
GWSVC62	18	457	36 <td 914	52	1320	Blue Cart Cover — Tall Unit	3.5	1.6	
*GWOLYKIT							Tote Glassware Transport Kit	38.0	17.0
GWBSKT36	18	457	35 1/2	901	7	178	Vinyl-Coated Baskets (2)	8.0	3.6

*Each Metro tote kit includes TB93060NAT (1), TB92060NAT (1), DL93060NAT (3), DS93060NAT (3), DS92060NAT (3), and DL92060NAT (3).



Red shelf markers can be used to designate unclean glassware



Blue shelf markers can be used to designate clean glassware

By combining standard MetroMax components, including Max baskets, a custom glassware cart can be created. Contact your Metro representative for more information.



LABORATORY SOLUTIONS — JUST ADD CASTERS



High Performance Liquid Chromatography (HPLC) Carts

- HPLC carts contribute to greater benchtop productivity.
- Mobilize and stack HPLC equipment on carts to maximize valuable lab space.
- Avoid crowding valuable bench top space with High Performance Liquid Chromatography (HPLC) or other analytical equipment.

HPLC Models (Casters not included*)

Cat. No.	Width		Length		Height		Description	Approx. Pkd. Wt.	
	(in.)	(mm)	(in.)	(mm)	(in.)	(mm)		(lbs.)	(kg)
HPLC3X2	24	610	30	760	81	2288	4-Shelf Unit Single Experiment Cart	70	32
HPLC4X2	24	610	48	1219	81	2288	4-Shelf Unit Double Experiment Cart	101	46

*See page 3 for Caster Selection Guide.

Accessories

Cat. No.	Description	Approx. Pkd. Wt.	
		(lbs.)	(kg)
FMAX	Post-Mount Swing Arm for Flat Monitor	4.5	2.0
TMX	Post-Mount Cable/Tube Management Clips (6 clips/bag)	1.0	.45

Original HPLC Models (Include casters)

Cat. No.	Width		Length		Height		Description	Approx. Pkd. Wt.	
	(in.)	(mm)	(in.)	(mm)	(in.)	(mm)		(lbs.)	(kg)
HPLC1X2	24	610	30	760	81	2288	5-Shelf Unit Single Experiment Cart	89.5	40.6
HPLC2X2	24	610	48	1219	81	2288	5-Shelf Unit Double Experiment Cart	114.5	51.9

Note 1: Single HPLC experiment carts feature a 24"x30" (610x760mm), five-shelf unit (4 solid, 1 open-grid shelf), mounted on 74" (1880mm) mobile posts. Double HPLC experiment carts feature a 24"x48" (610x1219mm), five-shelf unit (4 solid, 1 open-grid shelf) mounted on a 74" (1880mm) mobile posts.

Note 2: Metro Olympic tote boxes can be used to complete the system, either on the bottom shelf to contain test beakers or flasks, or in conjunction with an Undershelf Slide to provide a drawer for small tool storage.

Other Accessories

• Slide-out Keyboard Shelf

Epoxy-coated keyboard shelf provides high level of corrosion resistance. Designed to fit both 18" (457mm) and 24" (610mm) wide MetroMax shelves. Keyboard shelf loading should not exceed 10 lbs. (45.8kg). Dimensions: 16"W.x26¹/₂"L.x5"H. (406x673x127mm)

• Flat Monitor Mounting Kit

Unique mounting bracket and cross-bar design permits flat monitor to be mounted on MetroMax units. Flat monitor can be mounted between two MetroMax posts, either in back or front of unit. Mounting bracket loading should not exceed 30 lbs. (14kg). VESA mounting plates included.

Bracket Dimensions:
3⁷/₁₆"W.x8¹³/₁₆"L.x5³/₄"H. (87x223x146mm) (Cat. No. FMBX)

Cross-Bar Dimensions:
2¹/₈"W.x30"L.x3"H. (54x762x76mm)
2¹/₈"W.x36"L.x3"H. (54x914x76mm)
2¹/₈"W.x48"L.x3"H. (54x1219x76mm)

Note: For flat monitor mounting on MetroMax order either Cat. No. FM30X, FM36X, or FM48X (Cross-bar and mounting bracket included). For flat monitor mounting on Mobile Desk order Cat. No. FMBX.

• Power Strip

Six outlet power strip, featuring surge protection, mounts flush with any MetroMax shelf frame. Power strip is UL approved. Gray power strip comes with 6 foot (1829mm) long cord.

Dimensions: 2¹/₄"W.x13"L.x4¹/₄"H. (57x330x108mm)



FMAX and TMX

HPLC3X2
(Shown with accessories and casters)



Cat. No. KBX



Cat. Nos. FM30X/
FM36X/FM48X
(Cross Bar and Mounting
Bracket included)

Usage Instruction

- When flat monitor mounting kit is in use, please remove flat monitor from cross bar before cart transport.



Cat. No. PSX

LABORATORY SOLUTIONS

MetroMax® Lab Carts

Metro's Lab Cart line includes a General Lab Cart, Chemical Cart, and Mobile Desk. All carts are designed to offer superior corrosion resistance. Smooth rolling, 5" (127mm) polyurethane casters come standard with each cart. All shelves adjust in 1/2" (12.7mm) increments, offering precise shelf adjustment and maximum storage utilization.



Mobile Desk
Cat. No. MDSX2
(Casters included)

- Mobile Desk can be used for instrumentation storage or can be combined with accessories to provide a functional lab work surface.
- Accessorize desk with power strip, slide-out keyboard, and flat monitor mounting.
- Four, locking 5" (127mm) polyurethane casters included for maximum stability.



General Lab Cart
Cat. No. LABX2
(Casters included)

- Shelf mats have built-in Microban® antimicrobial product protection.
- Microban® protects the shelf mats from bacteria, mold, mildew and fungi that cause odors, stains and product degradation.
- Cart is ideal for transporting equipment and instruments in and around lab.
- Two brake casters provided for extra stability.



Chemical Cart
Cat. No. CHEMX2
(Casters included)

- Solid shelves contain unwanted spills.
- Stackable perimeter ledges retain chemicals, acid and other solution containers for safe transport.
- Solid shelf mats lift off shelf frame for easy cleaning.
- 5" (127mm) polyurethane casters provide smooth ride.
- Two brake casters provided for extra stability.

Dimensions

Cat. No.	Width		Length		Height		Cart Load Rating		Description	Approx. Pkd. Wt.	
	(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	(lbs.)	(kg)		(lbs.)	(kg)
LABX2	18	457	36	914	40	1016	600	273	General Lab Cart	43	19.5
CHEMX2	18	457	36	914	40	1016	600	273	Chemical Cart	49	22.2
MDSX2 ¹	18	457	36	914	40	1016	600	273	Mobile Desk	55	24.9

¹ Mobile desk features a phenolic work surface offering a high level of corrosion resistance. Mobile desk includes: four polyurethane brake casters, each measuring 5" (127mm), for maximum stability when foot-operated brakes are engaged.

Note: All carts include 5MPX series casters (2 brake, 2 swivel), unless otherwise noted.

Job _____



LABORATORY SOLUTIONS — POLY

DEEP LEDGE LAB SOLUTIONS with



- **Safe and Easy to Clean**
- **Strong and Durable**
- **Versatile**

Metro Deep Ledge Carts with Microban® antimicrobial product protection are the most advanced general purpose carts in the marketplace today. The Deep Ledge series has shelves with built-in Microban® antimicrobial product protection that helps keep shelves cleaner between cleanings by inhibiting the growth of bacteria, mold and mildew that cause odors and stains on the shelf surface.

All models listed below come without casters. Refer to Caster Selection Guide on page 3 to select casters.

Cat. No.	Width (in.) (mm)	Length (in.) (mm)	Height (in.) (mm)	Description	Approx. Pkd. Wt. (lbs.) (kg)
LDP	21½ 546	32¾ 831	41 1041	Lab Dolly with Stainless Posts and Handle	25 11
LC2P2030	21½ 546	32¾ 831	41 1041	2-Shelf Cart with Stainless Posts and Handle	29 13
LC3P2030	21½ 546	32¾ 831	41 1041	3-Shelf Cart with Stainless Posts and Handle	38 17


Note: Cat. No. LC3P2030 is load rated for a maximum of 200 lbs. (91kg).



LC3P2030
(Shown with stainless casters)



LDP
(Shown with stainless casters)



All Metro Catalog Sheets are available on our Web Site: www.metro.com



InterMetro Industries Corporation
North Washington Street, Wilkes-Barre, PA 18705
Phone: 570-825-2741 • Fax: 570-825-2852
For Product Information Call: 1-800-433-2232

L03-238
Printed in U.S.A. Rev. 8/05
Information and specifications are subject to change without notice. Please confirm at time of order.

Copyright © 2005 InterMetro Industries Corp.