



Item # \_\_\_\_\_

Job \_\_\_\_\_

## SUPER ERECTA SHELF® HI-RISE SHELVING

- **Efficient Light-Duty Storage:** Designed to work with “man aboard” stock picking equipment for light-duty storage applications.
- **Increases Valuable Storage Space:** By applying Hi-Rise components to Super Erecta Shelf wire shelves, you can easily construct shelving to a maximum of 24-feet high — three times the height of conventional shelving — thus making use of available air space.
- **Open-Wire Construction:** Permits air circulation and light penetration, reduces dust and moisture accumulation, and insures maximum efficiency of sprinkler system.
- **Fast, Easy Assembly:** Double-staked posts connect together easily, using double-threaded bolts. Split sleeve assembly device locks shelves in place in 1" increments along the height of the posts.
- **Increased Stability:** Cross bar kits, wall brackets, post clamps, and foot plates are available to increase the stability of one or more units.
- **Metro™ Computerized Engineering System:** Assures correct specifications and load ratings of Hi-Rise materials for the application at hand.

**All Hi-Rise applications must be reviewed and approved by InterMetro Engineering.**



**InterMetro Industries Corporation**  
North Washington Street  
Wilkes-Barre, PA 18705  
[www.metro.com](http://www.metro.com)

Copyright © 1999 InterMetro Industries Corp.



**Hi-Rise Shelving**

**10-17**

Job \_\_\_\_\_



## SUPER ERECTA SHELF® HI-RISE SHELVING

The Super Erecta Shelf system can be accessorized with the components listed below to construct Hi-Rise shelving. See your Metro™ representative for details.

**For ordering purposes, use Hi-Rise price sheet in conjunction with Hi-Rise selection guide.**

### Double-Staked Posts — Chrome-Plated

| Length<br>(in.)                  | (mm) | Cat. No. |
|----------------------------------|------|----------|
| 13 <sup>7</sup> / <sub>8</sub>   | 356  | HR13PC   |
| 33 <sup>7</sup> / <sub>8</sub>   | 864  | HR33PC   |
| 53 <sup>15</sup> / <sub>16</sub> | 1371 | HR54PC   |
| 61 <sup>15</sup> / <sub>16</sub> | 1575 | HR63PC   |
| 74                               | 1880 | HR74PC   |
| 86                               | 2184 | HR86PC   |
| 96                               | 2438 | HR96PC   |



### Double-Threaded Bolt Cat. No. DTBZ



### Cross bar Kit Cat. No. HRCBN (Not UPS Shippable)



### Wall Bracket Kit Cat. No. HRWBC



### Hi-Rise Square Foot Plate Cat. No. HRFPPZ



### S-Hook Cat. No. 9995Z



### Hi-Rise Top Cap Cat. No. HRTCP



### Post Clamp Cat. No. 9994Z



**NOTE 1:** All Hi-Rise applications **must** be reviewed and approved by InterMetro Engineering.

**NOTE 2:** Hi-Rise **wire** shelving systems can be used specifically to store large amounts of lightweight parts, such as electronic components, small sub-assemblies, or finished goods. It is designed to work with "man aboard" stock pickers, but Hi-Rise is not designed to accommodate pallet racks, skids, or fork lift equipment.

**NOTE 3:** To protect the Hi-Rise system from damage by motorized material handling equipment, a floor-mounted steel guard is required.

**NOTE 4:** Hi-Rise uses wire shelves only.

Manufactured by:



### InterMetro Industries Corporation

North Washington Street, Wilkes-Barre, PA 18705

Phone: 570-825-2741 • Fax: 570-825-2852

For Product Information Call: 1-800-433-2232

Visit Our Web Site: [www.metro.com](http://www.metro.com)

L02-013  
12/99  
Printed in U.S.A.

Information and specifications are subject to change without notice. Please confirm at time of order.